



Monocrystalline 33-cell Module

BE Series 160W | 0-3% Positive Tolerance



GARANTÍA DE RENDIMIENTO LINEAL LINEAR PERFORMANCE WARRANTY



25Years Enhanced Product Warranty on Materials and Workmanship
30Years Linear Power Performance Warranty



High efficiency

PERC technology improves efficiency, increases power generation, and contributes to lower LCOE.



Lower heat spot Risk

Innovative circuit design and "HalfCell" structure decrease the temperature of heat spots and effectively reduce power loss.



Excellent low-light performance

Reliable performance in low-light conditions such as in the morning, at dusk or during raining days.



Resilient to extreme weather

Carefully selected materials ensure the module still works well under the condition of 2400Pa wind load and 5400Pa snow load.



PID resistant

High quality solar cell and advanced processing technology contribute to excellent PID resistance performance.



Bloomberg
NEW ENERGY FINANCE



Anti-PID
System voltage durability
PPP 56042



+34 985 194 232



www.bexieenergy.com



Calle Peña Santa 68, Polígono Industria
Silvota, 33192, Llanera, Asturias

Technical specifications

battery module	Monocrystalline silicon photovoltaic cell module
Quality level of battery cells	A-level
Peak parameters at AM1.5, 1000w/m ² irradiance, and 25°C battery temperature:	
Standard power	160W
Optimal power point voltage v _{mp} (V)	18V
Optimal power point current I _{mp} (A)	8.89A
Short circuit current I _{sc} (A)	9.36A
Open circuit voltage V _{oc} (V)	23V
system voltage	Maximum system voltage 1000VDC
Cell conversion efficiency	≥23%
Peak power temperature coefficient (%/k)	(0.5±0.05)%/°C
Short circuit current temperature coefficient (%/k)	(0.06±0.01)%/°C
Open circuit voltage temperature coefficient (mV/k)	-(155±10)mv/°C
Working temperature range	-40 to +85°C
Power error range	±3%
solar cell	Monocrystalline silicon wafer 210mm* 105mm
Number and arrangement of batteries	thirty-three
connector	MC4
Protection level of junction box	IP65
Connection wire length of junction box	Positive electrode 750mm, negative electrode 750mm, 4.0mm ²
Component size	1200*670*30mm
Tempered glass	1195*665*3.2